




Parquet Floors



Product data sheet and technical information

Update: August 2012

Pure Collection, Sensual Collection, Bright Collection, Straight Collection

| | | |
|--|---|---|
| Grading | Manufacturing grading (Peaceful, Balance, Expressive) |    |
| Dimensions | parquet floor 1-strip 2390 x 200 x 13 mm | |
| Profile | CLICKitEASY | |
| Product constructions | approx. 3,5 mm wear surface/ solid softwood staves in the middle layer with HDF-board-inserts at each end/ stabilizing layer of pine veneer | |
| Packing unit | 7 pieces per carton (approx. 3.346 m ²) 35 cartons per pallet (approx. 117.11 m ²) | |
| Product quality tested by | eco-Umweltinstitut Köln | |
| Surface-treatments | natural oil-treated | |
| Guarantee | 30 years for private use according to our separate terms of guarantee | |
| Block variation of strips in width | ± 2 mm | |
| Humidity level on delivery according to DIN EN 13489 | 7% ± 2% | |
| Stain resistance according to EN 717 - 2 | 1C | |
| Formaldehyde emission according to EN 717 - 2 | Class E1 (< 3,5 mg/(h x m ²)) | |
| Thermal resistance according to DIN 4108-4 | ca. 0,091 m ² K/W | |
| Resistance to chair castors according to EN 13329 | No change if soft chair castors are used (Type W) | |
| Grading specifications according to EN 13487 | Request are fulfilled by manufacturing gradings | |
| laying system (laying procedure) | Floating, overall glued | |
| floor heating (underfloor heating) | Only suitable for hot water underfloor heating with a maximum surface temperature of 24°C. | |

General requirements according to European Standard EN 13489

| | |
|---------------------------|---------------|
| Differences in width | ± 0,20 mm |
| Transverse wrapping | < / = 0,40 mm |
| Differences in height | < / = 0,20 mm |
| Squareness of the element | < / = 0,40 mm |