

Product data sheet and technical information parquet floors base.59

Product range	base.59 14 mm
---------------	---------------

Product data

	plank
Dimensions in mm (L * W * T)	1900 x 190 x 14
Wear surface	approx. 3,0 mm
Units / package	8 pieces
Package	2,889 m ² ; 22,550 kg
Warranty	15 years for private use according to our terms of warranty
Connection	ClickTec
Notes	Subject to technical changes, Cleaning and care see instructions please

Product constructions

Wear surface	Hardwood
Middle layer	softwood staves
Stabilizing layer	poplar

Product properties

	Test norm	
Thermal resistance	DIN EN 4108-4	0,13W/mK
Biological durability		class 1
PCP content		≤5 ppm
Formaldehyde emission	EN 717 - 2	E1
Reaction to fire	EN 13501-1	Dfl-s1
Resistance to chair castors	DIN EN 13329	No impact if soft chair castors are used
Sorting requirements	EN 13489	Requirements are met by factory sorting
Laying system	EN 13489	floating, overall glued
Floor heating		Only suitable for hot water underfloor heating with a maximum surface temperature of 29°C
Renovation		At least resandable twice with normal wear
Disposal		Private disposal in the garbage possible

Tolerances according to EN 13489

allowed differences in width	± 0,2 mm
allowed differences in squareness	≤ 0,2 %
longitudinal curvature	≤ 0,1 %
Transverse curvature	≤ 0,2 %
Differences in height	≤ 0,2 mm
Humidity level on delivery	5-9%

Surface properties

	Test norm	laquered	natural oil treated	natural oil treated, brushed
slip resistance	EN 15676	USRV 70	USRV 57	USRV 94
Resistance to staining	DIN 68861 - 1	1B	1C	1C
Scratch resistance	Hamberger Hobel	≥ 20 N	n.n	n.n

Due to its lively appearance, the grading is quite separate from conventional grading criteria.

Knots and splits are desirable visual characteristics of the grading, which when subjected to climate fluctuation can lead to the formation of cross going cracks

Product identification

		
---	---	---

Stand: 09.2016