

Parquet Floors



Product data sheet and technical information

Update: August 2012

Pure Collection, Sensual Collection, Bright Collection, Straight Collection

Grading	Manufacturing grading (Peaceful, Balance, Expressive, Impulsive)	  
Dimensions	planked floor, narrow 1180 x 110 x 11 mm	
Profil	ClickitEasy	
Product construction	approx. 2,5 mm hardwood wear surface; HDF middle layer; stabilizing layer of pine veneer	
Packing unit	8 pieces per carton (approx.. 1,0384 m ²) 64 pieces per pallet (approx. 66,4576 m ²)	
Product quality tested by	eco-Umweltinstitut Köln	
Surface treatment	matt lacquered	
guarantee	15 years for private use according to our separate terms of guarantee	
Block variation of strips in mm	---	
Humidity level on delivery according to DIN EN 13489	7 % ± 2 %	
Scratch resistance	>/= 20 N (Hamberger Hobel)	
Stain resistance according to DIN 68861 - 1	1B	
Formaldehyde emission according to EN 717 - 2	Class E 1 (< 3,5 mg/(h x m ²))	
Thermal resistance according to DIN 4108-4	Parquet floors approx. 0,066 m ² K/W	
Resistance to chair castors acc. to DIN EN 13329	No change if soft chair castors are used (type W)	
Grading specifications acc. to EN 13489	Requests are fulfilled by manufacturing gradings	
Laying system (laying procedure)	Floating, overall glued	
Floor heating (underfloor heating)	Only suitable for hot water underfloor heating with a maximum surface temperature of 24°C.	

General requirements according to European Standard EN 13489

Differences in width according to EN 13489	± 0,20 mm
Transverse warping according to EN 13489	</= 0,40 mm
Differences in height according to DIN EN 13489	</= 0,20 mm
Squareness of the element acc. to DIN EN 13489	</= 0,40 mm